










Intended use

Mipa Kunststoffreiniger is a CFC-free cleaning agent for all common plastics. It eliminates electrostatic charges and prevents their regeneration. Electrostatic charge causes higher dust attraction during the coating of plastic parts. This product can be applied by paintbrush, brush, wipe, sponge and by spray gun.

Spreading rate: --

Processing instructions

	Colour colourless					
	Mixing ratio					
	Hardener		by weight (lacquer : hardener)		by volume (lacquer : hardener)	
	--	--	--	--	--	--
	Hardener					
	for complete paintwork				for partial paintwork	
	--	--	--	--	--	--
	Pot life					
	--	--	--	--	--	--
	Thinner					
	--	--	--	--	--	--
	Spray viscosity					
	Gravity spray gun				Airmix/Airless	
	--	--	--	--	--	--
	Application method					
	Application method	Hardener	Pressure (bar)	Nozzle (mm)	spray passes	Thinner
	--	--	--	--	--	--
	Flash-off time					
	--	--	--	--	--	--
	Dry coat thickness					
	--	--	--	--	--	--
	Drying time					
	Object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
	--	--	--	--	--	--

Note

- Storage:** at least 4 years in unopened original containers.
- VOC Regulation :** EU limit value for this product (category B/a): 850 g/l
This product contains max. 747 g/l of VOC.
- Processing conditions:** from +10° C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
- Processing instructions:** Please see technical data sheet L7 „coating plastics“. The temperature in the booth and of the material should be between 18 - 24 °C. Use always two different, clean clothes: one for applying the product and one for rubbing dry.