

Special thinner for Mipa BC 2-layers metallic basecoat, used to improve the orientation of the effect pigments. To best bring out the alu-effect, it is advisable to use Mipa Stabilisier-Verdünnung especially in paints with a pronounced tendency to clouding.

Colour shade	milky			
Mixing ratio	2 : 1 (Mipa BC : Stabilisier-Verdünnung)			
Hardener				
Thinners				
Spraying viscosity 20°C				
Application	spraying pressure	spraying nozzle	spraying operations	
Air / Flowjar - Spray gun				
Airless / Airmix				
Pot life				
Coat thickness / dry film				
Curing time / Flash off time				
Dry	recoat time	dust dry	set to touch	full hardness
Object temp. 20°C				
Object temp. 60°C				

**Recommendations:**

Keep container tightly closed. Keep away from sources of ignition, or from combustible materials. Take precautionary measures against static discharges.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!

This data sheet is for information purpose only! To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty. Please follow recommendations stated on the relevant safety data sheet and precautions stated on the product label. We reserve our right to make additions, deletions, or modifications to the information at any time without prior notification.